



<h2 style="color: red;">WebEnv-Smart</h2> <p>TCP/IP Environment Security</p>	
------------------------------------------------------------------------------	------------------------------------------------------------------------------------

### Description

WebEnv-Smart 是整合WebEnv Family 產品所研發設計之智慧型環境監控主機，產品提供溫度、DI 與 DO之連動本地報警、網路遠端報警、提供多點監控整合標準、可整合各種通訊系統之輸出報警點、火警盤、消防盤、電力盤、SMR及UPS等各種環境監控設備之報警整合，內建ARM-7 32bit CPU 10/100M TCP/IP 網路傳輸功能。19” 機架式設計適用於電信及電腦機房使用、內建溫度及溼度偵測可設定兩段式報警、可配合溫度過高啓動冷氣、風扇等設備對於IDC、無人機房控管有相當大之幫助、並可以透過遠端開啓相關設備

DI 輸入可整合DVR數位錄影、門禁系統、消防系統等告警訊息等達到遠端網路監控功能。

### Advantages

- BS7799 資訊安全企業資訊化最佳方案
- 低成本，高可靠，易管理的網路型環境監控管理系統
- 管理軟體支援遠端開啓、Log 事件紀錄
- 支援 chico 堆疊串接擴充 I/O



Item	Warning	Device	Class	Menu	Time
1	#	sevio-1	DO	DO action! * DO D14 Off	2004/1/08 上午 09:25:2
2	#	sevio-1	DO	DO action! * DO D14 Off	2004/1/08 上午 09:25:1
3	#	sevio-1	DO	DO action! * DO D14 Off	2004/1/08 上午 09:24:5
4	#	sevio-1	DO	DO action! * DO D13 Off	2004/1/08 上午 09:24:5
5	#	sevio-1	DO	DO action! * DO D12 Off	2004/1/08 上午 09:24:5
6	#	sevio-1	DO	DO action! * DO D11 Off	2004/1/08 上午 09:24:5
7	#	sevio-1	DO	DO action! * DO D04 Off	2004/1/08 上午 09:24:5
8	#	sevio-1	DO	DO action! * DO D03 Off	2004/1/08 上午 09:24:5
9	#	sevio-1	DO	DO action! * DO D02 Off	2004/1/08 上午 09:24:5
10	#	sevio-1	DO	DO action! * DO D01 Off	2004/1/08 上午 09:24:5
11	#	sevio-1	DO	DO action! * DO D14 Off	2004/1/08 上午 09:24:3
12	#	sevio-1	DO	DO action! * DO D13 Off	2004/1/08 上午 09:24:3
13	#	sevio-1	DO	DO action! * DO D12 Off	2004/1/08 上午 09:24:3
14	#	sevio-1	DO	DO action! * DO D11 Off	2004/1/08 上午 09:24:3
15	#	sevio-1	DO	DO action! * DO D04 Off	2004/1/08 上午 09:24:3

# Specifications

Built in Sensor	
Built in Sensor Channels	2 (Temperature , Humidity )
Temperature range measured	0 ~ 50° C with +/- 1°C accuracy
Humidity range measured	20 ~ 90% RH with +/- 3 % accuracy
Digit Output Event Trigger	Build in Temperature & Humidity two Level Threshold Event Trigger DO Alarm Output with DI / Temp / Hum
Digital Input/output	4 in 4 out Terminal screw barrier block with LED Status indicators
CPU	32-bit ARM7, 50MHz
Network Interface	10/100 Base-Tx RJ-45 connector
Protocol	ARP, IP, ICMP, UDP, TCP, HTTP, DHCP
Security	HTTP Browser Setup, Password & Connect Password
Switching Power Supply	Input : 90 ~ 240 VAC, 60/50 Hz
LCD Panel	Real time Status on 16*2 LCD Panel
KeyPad	4 button key Query for Panel Setup
Mounting	EIA/TIA 19" 1U Rack
Operator Environment	Temperature : 0 ~ 50      Humidity : 10 ~ 90 %RH

## Order Information

WebEnv-W30001-001 : Webenv-smart network controller 4DI/4DO

WebEnv-W30001-002: Webenv chico controller

WebEnv-S10001-001 : WebEnv2000 Manager 10 socket