



Webenv usbview is a compact web-server of remote video surveillance . it can be accessed from anywhere in the world via Internet By Browser. Also Advance Integrated with WebEnv2000 for Server Room Monitoring surveillance.

iCV-12 Webenv usbview

Technical Specification

- Build-in Web Server
- 10/100Mbps Fast Ethernet Network Access
- 32-Bit RICS CPU 50MHz
- 1MB Flash Memory
- 8MB Dynamic Memory
- 5.3V DC 1A Maximun
- Operation Temperature : 0 – 50
- Operation Humidity: 10% - 90%
- Rackmount Embedded Module or stand-alone for Indoor Using only
- Network Protocol: HTTP , TCP/IP , UDP , SMTP ,PPPoE , DDNS , DNS Client , Sntp , DHCP , FTP ,SNMP



Video Specification

- Support All USB PC Camera with VIMICRO ZC0301Plus processor built-in
- Resolution: 640X480 , 320X 240 , 160X120
- Frame Rate : Up to 20 at 320X240
- MJPEG compression
- 2 USB Ports for PC Camera
- USB 1.1 & 2.0 compliant
- Can combine 2 different kind of USB PC Camera
- Support Pan/Tile USB PC Camera, Infrared USB PC Camera

CM-01 USB PC Camera

- VIMICRO ZC0301Plus processor inside
- Color CMOS VGA Sensor with 350,000 pixels
- Infrared LED to aid night vision (up to 2.0 Meter)



- Up to 30fps@CIF(352 X 288) ,10-15fps@VGA(640 X 480)
- USB Interface ,Compliant with USB 1.1 Specification
- Focus Distance: 5cm to infinity ,Adjustable Focus Lens
- Visual Angle: 51/60 degree horizontal
- Auto Control : White balance , Exposure , Color / Brightness
- Operation Temperature : 0 – 40
- Dimension: 35(W) X 75 (H) X 57 (D)
- Weight: 150g

CM-03 USB PC Camera

- High Speed Pan and Tilt USB PC Camera
- Pan:320°@ 90°/sec and Tilt 60°@90°/sec
- USB Controlled Pan/Tilt, RS232 Port not required
- VIMICRO ZC0301Plus processor inside
- Color CMOS VGA Sensor with 350,000 pixels
- Up to 30fps@CIF(352 X 288) ,10-15fps@VGA(640 X 480)
- USB Interface ,Compliant with USB 1.1 Specification
- Focus Distance: 5cm to infinity ,Adjustable Focus Lens
- Minimun Illumination : 2.5 lux@ f1.4
- Visual Angle: 51/60 degree horizontal
- Auto Control: White balance , Exposure , Color / Brightness
- Operation Temperature : 0 – 40
- Dimension: 110(W) X 112 (H) X 106 (D)
- Weight:400g



WebEnv2000 Software manager

